

APPLICATION

- This Keyboard is mainly targeted for use for unsupervised or semi-supervised positions of varied access applications, internet terminals and information kiosks at universities, shopping malls, hotels, banks, airports, railway-stations and other public areas, ticket vending machines, gas stations, cash machines (ATMs/CDM), Internet public phones etc.

MAIN FEATURE

- The keyboard can be dynamic washable with water and other liquids, it can work well even under direct water pouring On the keyboard.
- The full keyboard can be locked/disabled via FN + Clean combination keys for easy cleaning without needing to take the keyboard away from PC.
- Imposing stainless steel design, specially designed keyboards meet the highest demands with regard to design, functionality, longevity and high protection level.
- Stainless steel fascia and key-tops guard willful destruction, vandal-proof, against corrosion, weather-proof especially under extreme climatic conditions, water proof/dirt proof, operation under hostile environments.
- Waterproof execution according to IP67 protection from top panel, top stainless steel plate with flat keyboard surface for easy cleaning & threaded bolts for easy tightly mounting to enclosure or panel.
- An excellent tactile feel with short stroke switches and allow users to achieve stable and accurate data input, with firm tactile perception for comfortable operation
- Internet friendly key layout, key-tops are laser-etched in legends and characters for easy readability, long life to prevent lettering rub-off.
- Metal keys are protected against twisting and levering which can not be dislodged from front, or defaced removing key covers.
- Ease of customizing with multiple languages, to accommodate foreign or custom variants.
- Complete electronic modules including controller in close consultation with our customers are available.
- PS/2, USB connection plug-and-play with PC via PC existing OS driver, no needing of install separate driver.

MECHANICAL DATA

- Actuator/keys: 103 keys, 2.0mm thickness super quality SUS304 brushed stainless steel flat key.
- Key top style: Non-protuberant rectangular keys, laser engraved & etched legends & raised braille on keys are available
- Key Size: 14.0mm x 14.0mm for normal keys, 14.0mm x 28.0mm for enter key, 14.0mm x 70.0mm for space bar.
- Key travel: 0.45mm
- Actuation Force: 2.0N+/-0.1N for key 14.0mm x 14.0mm (pressure point) 4.0N+/-0.1N for key 14.0mm x 28.0mm (pressure point)
- Switch life: more than 5 million of operations.
- Front Plate: 1.5mm thickness super quality brushed stainless steel
- Back Plate: 3.0mm thickness brushed & oxidized aluminium
- Tracker ball: 38.1mm (1.5") diameter, IP68 dynamic 1200DPI laser trackball
- G.W.: 2.20KGs
- Dimensions:420.0mm x 145.0mm (L x W)



ELECTRICAL DATA

- Supply Voltage: +5V DC +/-5%
- Current Rating: appr. 30mA
- EMC Standard: It is compliance with the council IEC 61000-4-2:2008; IEC 61000-4-3:2006+AI:2007+A2:2010; IEC 61000-4-4:2004
- EMI: EN 55022: 2010
- EMS: EN 55024:2010
- Lifespan > 5 years
- Switch Contact Material: metal dome PCB with Gold-on-Gold key switch technology
- Interface: PS2, USB available.
- **OS: All windows, Linux, Unix, Mac OSX**

ENVIRONMENTAL ADAPTABILITY

- Operating temperature:-20°C to +60°C
- Storage temperature: -30°C to +70°C
- Operating RH: 30-90%
- Atmospheric pressure: 60-106Kpa.
- Saline mist: 96 hours, IEC 60512-6
- Damp heat test at + 40°C: 21 days, IEC 60512-6
- Dry heat test at + 85°C: 10 days, IEC 60512-6

RELIABILITY

- **RoHS Compliant, CE and FCC, ESD**
- **Protection Level: IP67(front panel)**
- **Vandal resistant IK10**
- Key Lifespan >5 million actuations
- MTBF >50000H
- MTTR <30min

