

# V-series

VESA mount panel PC's and monitors with full glass PCAP touch

- ✓ PCAP-touch with full tempered glass front for optimal scratch resistance
- ✓ Slim anodized aluminum bezel to protect the edges
- ✓ Without ventilation openings for use in dusty environments
- ✓ VESA 100 x 100 mm mounting points on the rear
- ✓ Available as panel pc or touchscreen monitor
- ✓ Panel pc available with Intel Celeron or Intel core-i5 processor
- ✓ Fanless, without moving parts for optimal reliability



## Specifications:

	V150	V170	V190	V215	V240
<b>Display size</b>	15" 4:3 (381 mm)	17" 5:4 (432 mm)	19" 5:4 (483 mm)	21.5" 16:9 (547 mm)	24" 16:9 (610 mm)
<b>Display resolution</b>	1024 x 768	1280 x 1024	1280 x 1024	1920 x 1080	1920 x 1080
<b>Active area</b>	304 x 228 mm	338 x 270 mm	376 x 301 mm	477 x 268 mm	531 x 299
<b>Measurements</b>	388 x 312 x 62 mm	426 x 358 x 65 mm	460 x 385 x 65 mm	561 x 352 x 65 mm	620 x 388 x 65 mm
<b>Touch</b>	PCAP touch, 3mm tempered glass in anodized aluminum bezel				
<b>CPU</b>	xxx-C4: quad core Intel Celeron J6412 with TPM2.0 xxx-51: quad core Intel core i5-8365U with TPM2.0 xxx-MON: touchscreen monitor without pc				
<b>Memory</b>	Standard 8GB DDR4, maximum 32GB (for panel pc only)				
<b>Operating System</b>	Windows 10 IoT Enterprise 2021 LTSC, multi language, 64-bit (for panel pc only). Windows 11 optional.				
<b>Storage</b>	Standard 250GB SSD, other capacities optional (for panel pc only)				
<b>Connections</b>	xxx-C4: 2x 2.5Gb LAN, 1x USB 3.2, 3x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, IEC power connection xxx-51: 2x LAN (1x Gb, 1x 2.5Gb), 4x USB 3.1, 1x USB 3.1 type C, 2x COM, 1x HDMI, 1x DisplayPort, 1x audio out, IEC power connection xxx-MON: HDMI, DisplayPort, VGA, USB for touch, IEC power connection				
<b>Power Supply</b>	Internal 100-230V AC input				
<b>Operating temperature</b>	0-40°C				

Above products come with a 2 year carry-in warranty

Alternative dimensions, materials and design on request. Specification changes reserved

Visit the site for more  
product information

