

R-series

Panelmount touch screen PCs & monitors with anti-shatter foil

- ✓ PCAP touch with 3mm toughened glass and anti-shatter foil
- ✓ Anti-shatter foil avoids glass splinters in production environment in case of broken glass
- ✓ Stainless steel 316 panelmount with seamless front for optimal cleaning
- ✓ IP66 front with cell rubber gasket
- ✓ Easy mounting with clamp mounts
- ✓ Available as panel PC or touchscreen monitor
- ✓ Ideally suited for the food industry



Specifications:

	R150	R170	R190	R215	R240
Display size	15" 4:3 (381 mm)	17" 5:4 (432 mm)	19" 5:4 (483 mm)	21.5" 16:9 (547 mm)	24" 16:9 (610 mm)
Display resolution	1024 x 768	1280 x 1024	1280 x 1024	1920 x 1080	1920 x 1080
Active area	304 x 228 mm	337 x 269 mm	376 x 301 mm	476 x 267 mm	531 x 299
Front size	388 x 312 x 3 mm	426 x 358 x 3 mm	460 x 385 x 3 mm	561 x 352 x 3 mm	620 x 388 x 3 mm
Cut-out	369 x 293 mm	407 x 339 mm	441 x 366 mm	542 x 333 mm	601 x 369 mm
Touch	PCAP touch, 3mm tempered glass with anti-shatter foil in stainless steel 316 panelmount				
CPU	xxx-C4: quad core Intel Celeron J6412 with TPM2.0 xx-N1: quad core Intel N97 with TPM2.0 xxx-51: quad core Intel core i5-8365U with TPM2.0 xxx-MON: touchscreen monitor without pc				
Memory	Standard 8GB DDR4, maximum 32GB (for panel pc only)				
Operating System	Windows 10 or 11 IoT Enterprise 2021 LTSC, multi language, 64-bit (for panel pc only).				
Storage	Standard 250GB SSD, other capacities optional for panel pc only)				
Connections	xxx-C4: 2x 2.5Gb LAN, 1x USB 3.2, 3x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-N1: 1x 2.5Gb LAN, 1x 1Gb LAN, 2x USB 3.2, 2x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-51: 2x LAN (1x Gb, 1x 2.5Gb), 4x USB 3.1, 1x USB 3.1 type C, 2x COM, 1x HDMI, 1x DisplayPort, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-MON: HDMI, DisplayPort, VGA, USB for touch				
Power supply	panel PCs 9~24V DC with external adapter monitors 12V DC with external adapter monitors 24V DC with Phoenix connector				
Operating temperature	0-40°C				

Above products come with a 2 year carry-in warranty
Alternative dimensions, materials and design on request. Specification changes reserved.

Visit the site for more
product information

