

S-series

Panelmount panel PCs & touchscreen monitors with full glass PCAP-touch

- ✓ PCAP-touch with full tempered glass front for optimal scratch resistance
- ✓ Slim anodized aluminum bezel to protect the edges
- ✓ IP65 front with cell rubber gasket
- ✓ Easy mounting with clamp mounts
- ✓ Available as panel pc or touchscreen monitor
- ✓ Panel pc available with Intel Celeron or Intel core-i5 processor
- ✓ Fanless, without moving parts for optimal reliability



Specifications:

	S120	S150	S170	S190	S215	S240
Display size	12.1" 4:3 (308 mm)	15" 4:3 (381 mm)	17" 5:4 (432 mm)	19" 5:4 (483 mm)	21.5" 16:9 (547 mm)	24" 16:9 (610 mm)
Display resolution	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024	1920 x 1080	1920 x 1080
Active area	246 x 185 mm	304 x 228 mm	338 x 270 mm	376 x 301 mm	477 x 268 mm	531 x 299
Front size	302 x 232 x 10 mm	388 x 312 x 9 mm	426 x 358 x 9 mm	460 x 385 x 9 mm	561 x 352 x 9 mm	620 x 388 x 9 mm
Cut-out	282 x 212 mm	369 x 293 mm	407 x 339 mm	441 x 366 mm	542 x 333 mm	601 x 369 mm
Touch	PCAP touch, 3mm tempered glass in anodized aluminum bezel					
CPU	xxx-C4: quad core Intel Celeron J6412 with TPM2.0 xxx-51: quad core Intel core i5-8365U with TPM2.0 xxx-MON: touchscreen monitor without pc					
Memory	Standard 8GB DDR4, maximum 32GB (for panel pc only)					
Operating System	Windows 10 IoT Enterprise 2021 LTSC, multi language, 64-bit (for panel pc only). Windows 11 optional.					
Storage	Standard 250GB SSD, other capacities optional (for panel pc only)					
Connections	xxx-C4: 2x 2.5Gb LAN, 1x USB 3.2, 3x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-51: 2x LAN (1x Gb, 1x 2.5Gb), 4x USB 3.1, 1x USB 3.1 type C, 2x COM, 1x HDMI, 1x DisplayPort, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-MON: HDMI, DisplayPort, VGA, USB for touch					
Power Supply	panel PCs 9~24V DC with external adapter monitors 12V DC with external adapter monitors 24V DC with Phoenix connector					
Operating temperature	0-40°C					

Above products come with a 2 year carry-in warranty

Alternative dimensions, materials and design on request. Specification changes reserved.

Visit the site for more
product information

