

# S-series

Panelmount touch screen PCs & monitors with full glass PCAP-touch

- ✓ PCAP-touch with full tempered glass front
- ✓ Slim anodized aluminum bezel to protect the edges
- ✓ IP65 front with cell rubber gasket
- ✓ Easy mounting with clamp mounts
- ✓ Available as panel pc or touchscreen monitor
- ✓ Optimal scratch resistance



## Specifications:

	S120	S150	S170	S190	S215	S240
<b>Display size</b>	12.1" 4:3 (308 mm)	15" 4:3 (381 mm)	17" 5:4 (432 mm)	19" 5:4 (483 mm)	21.5" 16:9 (547 mm)	24" 16:9 (610 mm)
<b>Display resolution</b>	1024 x 768	1024 x 768	1280 x 1024	1280 x 1024	1920 x 1080	1920 x 1080
<b>Active area</b>	246 x 185 mm	304 x 228 mm	338 x 270 mm	376 x 301 mm	477 x 268 mm	531 x 299
<b>Front size</b>	302 x 232 x 10 mm	388 x 312 x 9 mm	426 x 358 x 9 mm	460 x 385 x 9 mm	561 x 352 x 9 mm	620 x 388 x 9 mm
<b>Cut-out</b>	282 x 212 mm	369 x 293 mm	407 x 339 mm	441 x 366 mm	542 x 333 mm	601 x 369 mm
<b>Touch</b>	PCAP touch, 3mm tempered glass in anodized aluminum bezel					
<b>CPU</b>	xxx-C4: quad core Intel Celeron J6412 with TPM2.0 xxx-N1: quad core Intel N97 with TPM2.0 xxx-51: quad core Intel core i5-8365U with TPM2.0 xxx-MON: touchscreen monitor without pc					
<b>Memory</b>	Standard 8GB DDR4, maximum 32GB (for panel pc only)					
<b>Operating System</b>	Windows 10 or 11 IoT Enterprise 2021 LTSC, multi language, 64-bit (for panel pc only).					
<b>Storage</b>	Standard 250GB SSD, other capacities optional (for panel pc only)					
<b>Connections</b>	xxx-C4: 2x 2.5Gb LAN, 1x USB 3.2, 3x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-N1: 1x 2.5Gb LAN, 1x 1Gb LAN, 2x USB 3.2, 2x USB 2.0, 1x COM, 1x HDMI, 1x VGA, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-51: 2x LAN (1x Gb, 1x 2.5Gb), 4x USB 3.1, 1x USB 3.1 type C, 2x COM, 1x HDMI, 1x DisplayPort, 1x audio out, 1x 2.54mm pitch connector for external power button xxx-MON: HDMI, DisplayPort, VGA, USB for touch					
<b>Power Supply</b>	panel PCs 9~24V DC with external adapter   monitors 12V DC with external adapter   monitors 24V DC with Phoenix connector					
<b>Operating temperature</b>	0-40°C					

Above products come with a 2 year carry-in warranty  
Alternative dimensions, materials and design on request. Specification changes reserved.

Visit the site for more  
product information

